



Technical Data Sheet

Attock Hidrive Supreme

Attock Hidrive Supreme is a superior high performance multi-grade motor Oil formulated to meet the requirements of passenger car engines requiring 20W 50 viscosity rating.

APPLICATIONS:

Attock Hidrive supreme is recommended for use in passenger car engines including Gasoline and turbocharged Diesel engines. The viscosity range of Attock Hidrive Supreme ensures quick circulation and easy cranking on startup, plus extra protection on high operating temperatures.

BENEFITS:

- Enhanced anti wear control, specifically in high performance engines.
- Enhanced engines deposit control.
- Enhanced high temperature oxidation control, which is necessary for engines operating under severe conditions at high temperature.
- Enhance safety against rust and corrosion
- Better and easy startup
- Better Oil consumption
- Improved control of volatility and oil consumption.

Typical Physical Characteristics:

HIPRODUCT	ASTM Methods	HIDRIVE SUPREME
API		SL/CF
SAE		20W-50
Appearance	Visual	Clear
Specific gravity at 60/60 °F	D 1298	0.869
Density at 85 °F	D 1298	0.860
Kinematics viscosity at 100 °C cSt	D 445	17.5
Kinematics viscosity at 40 °C cSt	D 445	140.4
Viscosity Index	D 2270	136
Flash point °C	D 92	250
Water by crackle test		Negative
TBN mg of KOH/gm	D 2896	8.3
Pour point °C	D 97	-24