



Technical Data Sheet

Attock Gear 85W-90 & Gear 85W-140 API GL-4

Gear 85W-90 & 85W-140 are made from high quality base oils and an additive system to provide excellent extreme pressure (EP) properties, wear resistance, oxidation stability, anti-rust and anti-corrosion qualities and protection against foaming. This lubricant provides excellent protection against shock loading as well as protection for the sealing materials.

APPLICATIONS:

Gear 85W – 90 & 85W 140 are recommended for use in bevel, spiral bevel and hypoid gear type differentials where the lubricant manufacturers specify API GL-4. This product may be used in the manual transmissions of passenger cars, light trucks or high performance cars. Manufacturers' recommendations should be followed as to SAE grade and ambient temperature.

BENEFITS

- Protect against rust and corrosion.
- Provides better low temperature fluidity protection than single grade oil
- Exceptional load carrying ability.
- Good oxidation stability.
- Extended transmission life.
- Smooth gearshift

Typical Physical Characteristics

GEAR 85W- 90 & 85W-140		
PRODUCT	GEAR 85W 90	GEAR 85W 140
API	GL 4	GL 4
SAE	85W 90	85W 140
Appearance	Clear	Clear
Specific gravity at 60/60 °F	0.899	0.905
Density at 85 °F	0.890	0.896
Kinematics viscosity at 100 °C cSt	17.0	27.5
Kinematics viscosity at 40 °C cSt	182	377
Viscosity Index	99	99
Flash point °C	210	230
water by crackle test	Negative	Negative
Pour point °C	- 27	- 27