



Technical Data Sheet

Attock Gold Turbo Plus

Attock Gold Turbo Plus is a top quality multi-grade heavy-duty Engine Oil developed from the latest concept of Lubricant Technology.

APPLICATIONS:

Attock Gold Turbo Plus fulfills most severe performance requirements of naturally aspirated, supercharged and turbocharged high output Diesel engines. It is also recommended for mixed fleet operators, for cars, trucks and buses.

BENEFITS:

- Maintains high engine cleanliness.
- Better control of deposits formation
- Longer oil life due to enhanced oxidation stability at high temperatures.
- Improved control of volatility and oil consumption.
- Improved anti wear properties.

Typical Physical Characteristics:

PRODUCTS	ASTM Methods	Attock GOLD Turbo Plus	Attock GOLD Turbo Plus
API		CH-4/SH	CH-4/SH
SAE		15W 40	20W 50
Appearance	Visual	Clear	Clear
Specific gravity at 60/60 °F	D 1298	0.890	0.894
Density at 85 °F	D 1298	0.881	0.885
Kinematics viscosity at 100 °C cSt	D 445	15.4	19.3
Kinematics viscosity at 40 °C cSt	D 445	113	168
Viscosity Index	D 2270	144	131
Flash point °C	D 92	220	240
Water by crackle test		Negative	Negative
TBN mg of KOH/gm	D 2896	10.0	10.0
Pour point °C	D 97	-24	-24