



Technical Data Sheet

Attock Hidrive Super SG/CD 20W-50

Attock Hidrive Super is a high performance multi-grade motor Oil especially designed for use in passenger car engines including Gasoline, and Diesel engines.

APPLICATIONS:

Attock Hidrive Super viscosity range ensures quick circulation and easy cranking on startup, plus extra protection on high operating temperatures. These features ensure full protection especially for engines operating in hot climate. Can be use where JASO MA2 recommended.

BENEFITS:

- Safeguard against soot, varnish, sludge formation, acid and corrosion.
- Better Oil pressure.
- Enhanced antiwear control, especially in high performance engines.
- Greater resistance to oxidation.

Typical Physical Characteristics:

PRODUCT	HIDRIVE SUPER	
	ASTM Methods	HIDRIVE SUPER
API		SG/CD
SAE		20W-50
Appearance	Visual	Clear
Specific gravity at 60/60 °F	D 1298	0.891
Density at 85 °F	D 1298	0.882
Kinematics viscosity at 100 °C cSt	D 445	18.30
Kinematics viscosity at 40 °C cSt	D 445	164.2
Viscosity Index	D 2270	124
Flash point °C	D 92	240
Water by crackle test		Negative
TBN mg of KOH/gm	D 2896	5.0
Pour point °C	D 97	-21