



## Technical Data Sheet

### Attock Gold Xtra CF/SF 20W-50

**Attock Gold Xtra** has distinct formulation, which ensures enhanced protection at high operating temperatures. These traits make it a better choice, particularly for engines operating in hot dusty climates.

#### **APPLICATIONS:**

**Attock Gold Xtra** is a high quality multi-grade Diesel Engine Oil Specifically recommended for use in heavy duty Diesel Engines as well as Turbocharged and naturally aspirated units.

#### **BENEFITS:**

- Improved piston and ring groove deposits control, Oil use control, and wear reduction.
- Longer engine and turbo charged life.
- Reduced inventory cost.
- Reduced operating cost.
- Adds to engine power retention and fuel efficiency.

#### **Typical Physical Characteristics:**

PRODUCT	ASTM Methods	ATTOCK GOLD Xtra
API		CF/SF
SAE		20W-50
Appearance	Visual	Clear
Specific gravity at 60/60 °F	D 1298	0.895
Density at 85 °F	D 1298	0.886
Kinematics viscosity at 100 °C cSt	D 445	19.1
Kinematics viscosity at 40 °C cSt	D 445	173.4
Viscosity Index	D 2270	122
Flash point °C	D 92	245
Water by crackle test		Negative
TBN mg of KOH/gm	D 2896	10
Pour point °C	D 97	-21